

# Industrial Floor Machines

## Triple planetary all Steel Gears.

The Koblenz 3 Idler Planetary gear drive assures a durable and smooth transmission of power from motor to pad driver. (TP & RM models)

### DURABLE ALL METAL CONSTRUCTION



- Cast iron chassis.
- Non marking sealed double ball bearing wheels and wrap around bumper guard.
- Hardened pinion gear.

### HIGH PERFORMANCE MOTOR



- Cool running, continuous operating heavy duty motor. The best modern technology can make. Will start with low voltage.

### SAFETY SWITCH AND LOCKING MECHANISM



- 13 Gauge chromed steel handle.
- Protection against operator error.
- No operator fatigue.



### EASY TO USE HANDLE CLAMP (TP models only)

- Simple, easy to operate and adjust.
- Smooth gliding on handle.
- Will lock to allow proper height adjustment of the handle.
- Large fine adjustment wheel and lock handle.

Part Number	Floor Machine Accesories
46-2751-9	46 lb. Floor machine weight
45-0449-4	4 Gallon solution tank.
45-0513-7	Pad driver 12" including clutch plate.
45-0432-0	Pad driver 16" including clutch plate.
45-0433-8	Pad driver 19" including clutch plate.
45-0503-8	16" Trilock™ pad driver.
45-0504-6	19" Trilock™ pad driver.
45-0434-6	Scrub brush 15"
45-0435-3	Scrub brush 18"
45-0436-1	Carpet brush 15"
45-0437-9	Carpet brush 18"

MODEL	BRUSH SPEED	PAD SIZE	MOTOR	SHIPPING WEIGHT	NET WEIGHT	SHROUD	
TP-1710	175 RPM	17 inches	1.0 H.P.	114 lbs.	89 lbs.	Reinforced	Cast iron
TP-2010	175 RPM	20 inches	1.0 H.P.	116 lbs.	99 lbs.	Epoxy	Cast iron
TP-1715	175 RPM	17 inches	1.5 H.P.	123 lbs.	96 lbs.	Powder	Cast iron
TP-2015	175 RPM	20 inches	1.5 H.P.	125 lbs.	106 lbs.	Coated	Cast iron
TP2S-2015-DC	320/175 RPM	20 inches	1.5 H.P. D.C. 2 speed	120 lbs.	101 lbs.	Steel	Cast iron
DP-1334	175 RPM	13 inches	3/4 H.P.	84 lbs.	61 lbs.	Aluminum	Aluminum
RM-1715	175 RPM	17 inches	1.5 H.P.	106 lbs.	81 lbs.	Polyethylene	Polyethylene
RM-2015	175 RPM	20 inches	1.5 H.P.	110 lbs.	86 lbs.	Polyethylene	Polyethylene

- Non marking bumper.
- Smooth glide vibration free operation!
- 50 ft. 3 wire grounded 14 gauge.
- Durable chromed 13" gauge steel 1 1/4" diameter.
- 5 inch non-marking 1 1/2" Axle with sealed double ball bearings.

THREE YEAR LIMITED WARRANTY ON MOTOR AND TRANSMISSION.  
THREE YEAR LIMITED WARRANTY ON PARTS AND WORKMANSHIP.

